



SPECIFICATIONS

This button is a highly vandal resistant button with essentially no moving parts. It is pressure activated, but can withstand an impact from a baseball bat or hammer. When the switch activates, you hear a beep and the LED lights and stays on until the walk cycle.

Body Material: Aluminum, Powder Coated

Colors: Black, Green & Yellow

To specify color, add B for black, G for green or Y for yellow in "X" position in part number.

Button Material: 316 Stainless Steel

Piezo Driven Solid State Switch:

Operating Force: 3 lbs. Maximum

Operating Temperature:  $-30^{\circ}\text{F}$  to  $165^{\circ}\text{F}$  ( $-34^{\circ}\text{C}$  to  $74^{\circ}\text{C}$ )

Operating Voltage: 18 VDC Nominal

Operating Life: Greater than 100 million operations.

Switch Hold Time: 6 Seconds Minimum

LED:

Operating Mode: Latching – Activates only during non-walk phases and stays on until the beginning of walk phase.

Requires Polara Latching Push Button Control Unit (LPBCU

Sold Separately) which is installed in the intersection control cabinet.

Luminous Intensity: Greater than 1200 mcd (ultra bright red)

Viewing Angle:  $160^{\circ}$

Beeper:

Sounds simultaneously with LED flash.

Different tones for press and release, 2.6 kHz & 2.3 kHz.

INFORMATION ON THIS DOCUMENT IS PROPRIETARY TO POLARA AND SHALL NOT BE USED, COPIED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT WRITTEN CONSENT OF POLARA.

Revised - 01/15/07										<b>POLARA ENGINEERING INC.</b> 4115 W. ARTESIA AVE. FULLERTON, CA. 92833 TOLERANCES: .XXX ±.005 .XX ±.02 (EXCEPT AS NOTED) SCALE 1:2			
DRAWN BY		CKR.		ENG. MGR.		MFG. MGR.		SHEET 1 OF 1					
DATE		DSN. ENG.		Q.A. APP.		FINAL APP.		USE					
04-03-03													
TITLE										DWG. NO.			
BULLDOG WITH LATCHING LED										BDLL2-X			
REV. DATE	LTR	E.C.O. NO.	BY	CKR	ENG	DSN	MFG	QA	FNL				