

Alpha Traffic Mini BBS

Alpha Traffic Mini Battery Backup Systems



Your Power Solutions Partner

- Consolidated battery backup system (BBS) designed to power ATC, NEMA M, P & 336 (or similar style) traffic controller cabinets
- Ideal solution for space constraint applications providing >4 hours of battery runtime*
- Self-contained UPS, factory wired, tested and ready to install, reducing installation time and cost**
- Alpha's "No Worries" 5 Year Warranty full replacement with AlphaCell™ 100XTV batteries
- Compact, integrated 350W or 1000W battery backup system, utilizing the same design and similar features of the highly successful and reliable FXM series UPS

Alpha Traffic Mini Battery Backup Systems (BBS) is a rugged enclosure made of 0.125" aluminum and designed to easily accommodate an Alpha uninterruptible power supply, Universal Automatic Transfer Switch and up to four AlphaCell™ 100XTV or two 195/220 GXL's. The Traffic Mini BBS is an outdoor-rated (NEMA 3R) enclosure. Features include: drop down lift off door, Type 2 Corbin lock, integrated document holder, tamper switch, wide range Automatic Voltage Regulation (AVR), remote monitoring/control and temperature compensated battery charging for extended battery life. The Alpha Traffic Mini BBS provides constant, reliable backup power for Traffic, ITS, Access Control, Security, Public Utility and Telecommunications applications in a compact, all-in-one enclosure. The Alpha Traffic Mini BBS series provides the same functionality as the Alpha class leading FXM Series, for lower power space constraint applications, in a single easy to install cabinet with a favorable curb appeal.

*runtime calculated with 450W resistive load with 4 x AlphaCell 100XTV at 25°C

**excluding batteries



Power



Alpha Traffic Mini Battery Backup System

| STANDARD FEATURES | | |
|--|--|--|
| <ul style="list-style-type: none"> • Integrated solution with uninterruptible power supply module, Universal Automatic Transfer Switch, document holder, battery cable kit and tamper switch • Two shelves for up to four AlphaCell™ 100XTV or two 195/220 GXL batteries • Can house optional Alpha Remote Battery Monitoring system • Mounting options include pole, wall, side or pedestal | | |
| MODEL | Traffic Mini 350 BBS | Traffic Mini 1000 BBS |
| Part Number | 0170021-040 | 0170021-010 |
| ELECTRICAL | | |
| System Input Voltage (Vac) | 120 | |
| Input Current Rating (A)* | 5.3 | 14 |
| Input Frequency (Hz) | 50/60 ±5% (Autosense) | |
| AVR Range (Vac) | 88-152 | 85-169 |
| System DC Voltage (Vdc) | 24 | 48 |
| Max Charge Current (A DC) | 6 | 10 |
| System Output Voltage (Vac) | 120 | |
| Output Power@ 50°C (Watts) | 350 | 1000 |
| Output Frequency (Hz) | = Input Frequency | |
| Output Voltage Regulation | ±10% Line Mode ±2% Inverter Mode | |
| Output Waveform | Pure Sine Wave | |
| MECHANICAL | | |
| Dimensions | in | 34H x 16W x 12D |
| | mm | 864H x 406W x 305D |
| Weight (without batteries) | 65 lbs (29.5 kg) | 55 lbs (25 kg) |
| Construction | Aluminum, 5052-H32 (High strength corrosion resistance) | |
| Finish | Natural Aluminum | |
| Cable Entrance | Bottom or Rear | |
| Mounting | Side mount, Optional - wall, pole or pedestal kit available | |
| Access | Removable bottom shelf for easy wiring access | |
| AC Input Connections AWG (mm ²) | Terminal blocks #14 to #6 AWG (2.08 to 13.3 mm ²) | |
| AC Output Connections AWG (mm ²) | Terminal blocks #14 to #6 AWG (2.08 to 13.3 mm ²) | |
| Dry Contact AWG (mm ²) | Terminal blocks #26 to #12 AWG (0.2 to 2.5 mm ²) | |
| COMMUNICATION INTERFACE | | |
| Display | 2 x 20 backlit alpha-numeric LCD | |
| Ports | USB-B Female: Local RS232 Communication RJ45: Remote Communication RJ11: Battery Temperature Compensation | USB: Local RS232 Communication RJ45: Remote Communication RJ11: Battery Temperature Compensation |
| Indicators | Green & Red LED's Solid Green: Line Mode Flashing Green: Inverter Mode Flashing Red: Alarm Solid Red: Fault | |
| Dry Contact | 2 x Programmable NO/NC (250Vac, 1A), 2 x user inputs | 5 x Programmable NO/NC (250Vac, 1A), 1 x 48Vdc/500mA, 3 x user inputs, 1 x ATS |


Alpha Technologies Ltd.

For more information visit www.alpha.ca

Canada: Burnaby, British Columbia T: 604.436.5900 F: 604.436.1233
United States: Bellingham, Washington T: 360.647.2360 F: 360.671.4936


#047-0314-00 Rev A (03/2017)

Alpha Technologies reserves the right to make changes to the products and information contained in this document without notice.
Copyright © 2017 Alpha Technologies. All Rights Reserved. Alpha® is a registered trademark of Alpha Technologies.
member of The Alpha Group™ is a trademark of Alpha Technologies.

member of The  Group™



Alpha Traffic Mini Battery Backup System

| MODEL | Traffic Mini 350 BBS | Traffic Mini 1000 BBS |
|--|---|--|
| Part Number | 0170021-040 | 0170021-010 |
| ENVIRONMENTAL | | |
| Temperature | Operating: -40 to 74°C (-4 to 165°F)** Storage: -40 to 75°C (-40 to 167°F) | |
| Relative Humidity | Up to 95%, non-condensing | |
| Altitude | Operating: Up to 2000m (6562ft) above sea level | |
| PERFORMANCE | | |
| Typical Output Voltage THD | <3% (resistive load) | |
| Typical Efficiency *** | Line Mode > 96% Inverter Mode > 82% | Line Mode > 92% Inverter Mode > 82% |
| Load Crest Factor | 3:1 (load dependent) | |
| AGENCY COMPLIANCE | | |
| Electrical Safety | UL1778, CSA 22.2 No 107.3, UL 60950-1, CSA-C22.2 60950-1 | |
| Marks |  | |
| EMC | CFR47, Part 15 Subpart B, Class A; CES-003 Class A | |
| NEMA | 3R | |
| STANDARD SYSTEM CONFIGURATION | | |
| 0.125" Thick Natural Aluminum Enclosure 350 or 1000W UPS Module Universal Automatic Transfer Switch Battery Cable Kit - ¼" Ring Lug Document Holder Door Filter Tamper Switch ADD AlphaCell Batteries - 4 x 100 XTV (Mini 1000 BBS) or 2 x 220 GXL (Mini 350 BBS) | | |
| OPTIONAL ACCESSORIES | | |
| Remote Battery Monitoring System Battery Heater Mats Mounting Brackets - Pole or Wall Pedestal Mounting Kit | | |
| *@ nominal input voltage and maximum battery charging current **Power module only. Output power derates above 50°C ***Efficiency is measured at an ambient temperature of 25°C, full resistive condition and nominal line and battery voltage | | |


Alpha Technologies Ltd.

For more information visit www.alpha.ca

Canada: Burnaby, British Columbia T: 604.436.5900 F: 604.436.1233
 United States: Bellingham, Washington T: 360.647.2360 F: 360.671.4936

#047-0314-00 Rev A (03/2017)

Alpha Technologies reserves the right to make changes to the products and information contained in this document without notice.
 Copyright © 2017 Alpha Technologies. All Rights Reserved. Alpha® is a registered trademark of Alpha Technologies.
 member of The Alpha Group™ is a trademark of Alpha Technologies.

member of The  Group™