



TEMPLE EDGE-LIT™ Internally-Illuminated LED Signs

RAZOR™
Side Access Illuminated LED Sign



PROVEN DESIGN

Just 1.6" deep. Weighs 5 lbs./sq. ft.

Designed to be the most durable illuminated street name sign on the market.

Slide-Lock mechanism gives the RAZOR adaptability for both single and double-sided applications while using the same sign frame.

UL Certified Class 2 Power Supplies and LEDs are fully accessible via the RAZOR's removeable end caps.

PROVEN QUALITY

Over 6 years in production, with over 10,000 units depolyed (formerly called the R409A).

Only a 0.5% failure rate (only 1 sign for every 200 shipped).

Temple ensures that each RAZOR sign is built to very rigorous quality standards and tested for 24 hours prior to shipment.

PROVEN PERFORMANCE

The RAZOR uses high-intensity LEDs rated for 60,000 hours-- over 14 years of maintenance-free illumination!

RAZOR's state-of-the-art LEDs are integrated into a rugged, thermally-designed circuit board that provides even illumination throughout the entire sign.

Meets or exceeds all industry standards for lux measurements.

www.temple-inc.com/edge-lit
800.633.3221

Temple Edge-Lit™ is a Division of Temple, Inc. © Copyright 2011. All rights reserved.



Integrity Service Relationships



QUALITYWORKS.



TEMPLE EDGE-LIT

Internally-Illuminated LED Signs



RAZOR

RAZOR Priority Regulatory Signs

COMMON SPECIFICATIONS	Internally-Illuminated LED Street Name Signs	Internally-Illuminated LED Regulatory Signs
MECHANICAL		
Dimensions:	Length 24" to 120" at 6" increments Height 15", 18", 20", 22", 24", 30"	Dimensions: Length MUTCD standard sizes from 18" to 36" (width) Height 18H" to 36H" Max
Thickness	1.6"	Thickness 1.6"
MATERIAL		
Frame	6000 Series Aluminum housing	6000 Series Aluminum housing
SIGN SHEETING		
Optional Sheeting	ASTM Type IX Retroreflective Sheeting (sign legend and background)	ASTM Type IX Retroreflective Sheeting (sign legend and background)
ILLUMINATION		
Contrast Ratio	Legend / Background contrast ratio 4:1 minimum	Legend / Background contrast ratio 4:1 minimum
FONTS		
Default	MUTCD Clearview Font, HWY E Series B, C, D, E Modified, Custom fonts available	MUTCD Clearview Font, HWY E Series B, C, D, E Modified, with Custom fonts available
ENVIRONMENTAL		
Wind Load	150 mph (241 km/h) with 1.14 gust factor and ice loading as per AASHTO LTS-4 2001	150 mph (241 km/h) with 1.14 gust factor and ice loading as per AASHTO LTS-4 2001
Electrical Certification	Listed to UL48	Listed to UL48
MOUNTING OPTIONS		
Under-hang Mount	Accepts Pelco SE-5015 or SE-5146	Accepts Pelco SE-5015 or SE-5146
Single-sided Fixed Mount	Accepts Pelco Astro-brac AS-3009 or equivalent	Accepts Pelco Astro-brac AS-3009 or equivalent
SIGN SHEETING		
3M™ Electrocut™ film	Yellow, Orange, Green, Black (Opaque), Red, Blue, Brown, and Clear 3M ScotchCal	Yellow, Orange, Green, Black (Opaque), Red, Blue, Brown, and Clear 3M ScotchCal
WEIGHT	Maximum of 7 lbs. per sq. ft., single and double-sided	Maximum of 7 lbs. per sq. ft., single and double-sided

©2011 Temple, Inc. All rights reserved.

Integrity
Service
Relationships



Forrest Temple
Temple Edge-Lit Accounts Manager
forrest.temple@temple-inc.com
256.221.7016 (mobile voice & text)

800.633.3221 toll free
256.353.4578 (fax)
www.temple-inc.com