

Power

Flextra Special Purpose Series

Side Mount and Battery Only Side Mount Enclosures



B4



S4

- Can be installed on any existing ground mount enclosure
- Engineered to minimize temperature differential between batteries
- Powder coat finish provides excellent corrosion protection
- Available in clear coat, seafoam green, pine green and gray
- B4 dimensions (in/mm): 19.5W x 48H x 8.75D/495W x 219H x 222W
- S4 dimensions (in/mm): 16.4W x 48.1H x 17.60D/417W x 1222H x 447W

Alpha's Flextra special purpose enclosures provide a cost-effective method of adding standby capacity to any installed ground mount enclosure. The Flextra B4 provides space to mount a 48V battery string, and for optimum battery life, has been engineered to minimize the temperature differential between batteries located within the existing enclosure and batteries in the B4. It can be mounted on either the right or the left side of the enclosure. The Flextra B4 kit includes the enclosure and door, key set, and all necessary mounting hardware and installation instructions.

The Flextra S4 enclosure is designed to fit on the side of most traffic controller cabinets. Any of Alpha Technologies's line of Novus UPS can fit inside, providing you with a range of backup power from 500 to 2200W. The Flextra S4 enclosure can accommodate a wide variety of AlphaCell™ batteries allowing you the maximum possible range of backup time for your system. The NEMA 3R rating means the enclosure is able to protect its internal components from the harsh outdoor environment.

For contact information visit www.alpha.com

The Alpha Group >

Europe, Middle East & Africa			Asia Pacific	North America	Latin & South America
Cyprus Tel: +357 25 375 675 Fax: +357 25 359 595	Germany Tel: +49 9122 79889 0 Fax: +49 9122 79889 21	Lithuania Tel: +350 5 210 5291 Fax: +350 5 210 5292	P.R. China Tel: +852 2736 8663 Fax: +852 2199 7988	Canada Tel: +1 604 430 1476 Fax: +1 604 430 8908	Contact USA office
Russia Tel: +7 495 916 1854 Fax: +7 495 916 1349	United Kingdom Tel: +44 1279 501110 Fax: +44 1279 659870			USA Tel: +1 360 647 2360 Fax: +1 360 671 4936	