

Model 206L

High Efficiency Power Supply

Plug-in Replacement for Caltrans Model 206 - CALTRANS QPL APPROVED

The EDI **Model 206L** is plug-in compatible with the Caltrans PDA #2 and PDA #3 found in 332 and 336 type cabinets using a Model 206 cabinet power supply. The **Model 206L** uses modern switching technology to replace the energy wasteful ferro-resonant technology of the Model 206.

The **Model 206L** provides full output regulation across changes in AC Line voltage and output load over the full operating temperature range of -34C to +74C. Power Factor Correction is also provided.

Caltrans QPL, TEES 2009 Compliant

MODEL 206L OPERATIONAL FEATURES

Basic Functions: The Model 206L provides a regulated 24 Vdc at 5 Amps over the full -34°C to +74°C (-30°F to

165°F) operating temperature range.

5 Amp Maximum Load Current

▼ Full Output Regulation +/- 2% over line and load

✓ High Efficiency

Power Factor Corrected

✓ Plug-in replacement for Caltrans Model 206

Display Indicators: Separate green LED indicators are provided to display AC input status, 24VDC output status

and associated fuse integrity.

Input Voltage Operating Range: 80 Vac to 270 Vac at 60 or 50 Hz

Power Factor Corrected (PFC): A Power Factor Correction circuit ensures a full load power factor of 0.98 or better, reducing

peak AC Line input current and associated stress on wiring. Inrush current limited.

Output Protection: The output is fused for over-current protection. The output is also protected against voltage

transients by a 1500 Watt suppressor.

Connector Input / Output Pins: Intermates with Beau S-5406 or equivalent:

Pin	Function	Pin	Function
7	+24VDC Output	10	No Connect
8	DC Ground	11	AC Neutral
9	Equipment Ground	12	AC Line +

Dimensions: 6.0 inches High x 5.5 inches Wide x 7.5 inches Deep excluding handle.

High Efficiency: With a 2.5 Amp load the Model 206L will

save an agency over 267 kWH of energy per year, resulting in a typical savings of \$27 per cabinet annually (@ \$0.10/kWH cost), when compared to a Caltrans Model 206.

Load	Model 206	Model 206L
1 Amp	43%	75%
2.5 Amp	60%	84%
5 Amp	69%	86%





Tel (480) 968-6407 Fax (602) 437-1996

