

TEMPLE, INC. MODEL 334 ITS FIELD CABINET

800.633.3221 www.temple-inc.com

Cabinet Dimensions: 66"H X 24"W X 30"D



Performance Features:

- Versatile product that can be used to house numerous ITS applications.
- Meets NEMA 3R requirements for cabinet enclosure.
- Constructed of 0.125" thick 5052-H32 aluminum.
- Door stops to hold the cabinet doors open at 90° and 120°.
- Three-point door locking system attached to each door.
- Full-size front and rear doors.
- 19" EIA equipment rack.
- Conforms to NEC wiring specifications.
- Dual thermostatically-controlled fans (100 CFM).
- Two 20W door actuated fluorescent lights.
- Weather and pest-resistant vent design.
- Pull-out drawer with hinged top included (25 pound capacity).

Optional Features:

- Generator Access Panel, located behind a lockable and weatherproof exterior door, allows restoration of Cabinet power by an external source when utility power is unavailable.
- External "Utility On" Indicator on the outside top of the Generator Access Compartment. The indicator will be visible outside the Cabinet from 30 feet away when turned on.
- Sunshields made from 0.125" 5052-H32
 aluminum alloy that have a 1" standoff from the
 outer surface of the Cabinet enclosure to absorb
 and reflect UV rays.

