



1.800.633.3221

www.temple-inc.com

# TEMPLE 336S ITS Field Cabinet

**NEMA 3R Rated Cabinet Enclosure**



**TEMPLE 336S Cabinet Dimensions:  
46.25H" x 24W" x 22.37D"**

## **Performance Features**

- Versatile product that can be used to house numerous ITS applications
- Made of 0.125" thick 5052-H32 aluminum alloy
- 2-point door locking system
- Full-size front and rear doors
- 19" EIA equipment rack
- Conforms to NEC wiring specifications
- Dual thermostatically-controlled fans (100 CFM)
- Two 20W fluorescent interior lights
- Weather and pest-resistant vent design
- Pole and pad mounts available
- Pull-out drawer with hinged top included (25 lb. capacity)

## **Optional Features**

- Generator Access Panel, located behind a lockable and weatherproof exterior door, allows restoration of Cabinet power by an external source when utility power is unavailable.
- External "Utility On" indicator on the outside top of the Generator Access Compartment. The indicator will be visible outside the Cabinet from 30 feet away when turned on.
- Sunshields are made from 0.125" 5052-H32 aluminum alloy, and have a 1" standoff from the outer surface of the Cabinet enclosure to absorb and reflect the sun's UV rays.

**Integrity  
Service  
Relationships**